

IP INTERCOMS with HD VIDEO

The **X-SERIES** of IP Video Intercoms are designed to provide HD video and reliable handsfree voice communication for SIP VoIP phone systems and service providers. The built-in IP video camera has H.264 video compression, low light sensitivity, a wide viewing angle of 126 degrees, and can output dual video streams of up to 1080p resolution.

The **X-SERIES** intercoms can dial programmable numbers and be programmed remotely via a built-in Web UI. On-board 2 Amp relay contacts are provided for activating door strikes or gate controllers.



X=SERIES FEATURES

- SIP compliant
- ONVIF Profile S compliant
- H.264 and MJPEG video encoding
- Up to 1080p SIP video calling
- Separate NVR stream with audio
- Selectable video resolutions: 352 x 288, 704 x 576, 720p and 1080p
- Remotely programmable via Web UI
- 2 Amp relay contacts
- PoE powered (class 2, < 6.5 Watts)
- Network downloadable firmware
- Cycles through backup phone numbers on busy or no-answer
- Diagnostics for testing microphone, speaker, and relay

ONVIF Profile S compliant

Protective
polycarbonate
camera window with
scratch resistant
coating and
water-tight gasket



Camera has a wide viewing angle of 126° (no fish eye!)

VIKING

(1)

Torx security screws

for vandal resistance

Heavy duty stainless steel push button switch

(#

Marine grade 316

stainless steel to

prevent corrosion

Mylar speaker with rubber gasket for a water-tight seal

Speaker screen helps prevent vandalism

Omni-directional microphone with water-resistant protection

Built-in LED lights steady to help locate the button in low light, flashes during dialing, then lights steady when answered

- Durable stainless steel construction for all models
- Wide operating temperature of -40° F to 140° F
- Volume adjustments for speaker and microphone
- Flush mount intercoms:
 X-35 Series
- Low profile surface mount intercoms: X-205 Series
- Surface mount emergency phones: X-1605



For outdoor installations, models with Enhanced Weather Protection (EWP) are available. EWP is perfect for applications where the unit is exposed to precipitation or condensation. EWP is designed to meet IP66 standards and may feature foam rubber gaskets, sealed connections, gel-filled butt connectors, as well as potted circuit boards.

For more info on EWP, scan here:





X-35-SS or X-35-SS-EWP

Brushed stainless steel finish.
Flush mount or use an optional surface mount box, sold separately.



X-35-BN or X-35-BN-EWP

Oil rubbed bronze finish. Flush mount or use an optional surface mount box, sold separately.



X-35-BK or X-35-BK-EWP

Textured black finish. Flush mount or use an optional surface mount box, sold separately.



X-205-SS or X-205-SS-EWP

Brushed stainless steel finish. Surface mount.



X-205-BN or X-205-SBN-EWP

Oil rubbed bronze finish. Surface mount.



X-205-BK or X-205-BK-EWP

Textured black finish. Surface mount.



X-1605 or X-1605-EWP

Emergency phone with HD video. Surface mount.





VIKING

Viking Electronics, Inc. 1531 Industrial Street Hudson, WI 54016-9386

TRIVIA QUESTION



What year was Viking Electronics started?

Everyone who submits the correct answer by 8/31/2023 will be entered into a prize drawing.

HOW TO | FAX: 715-386-4344 | SCAN -->
ANSWER | EMAIL: info@vikingelectronics.com



MAY-JUN Trivia: What red flower is a traditional symbol for Memorial Day? **Answer:** Poppy

Congratulations to BILL ESSARY from ESSARY COMMUNICATIONS!